

## Tuff-Edge® III Polyester Web Sling

- 30% more resistant to edge damage than our Tuff-Edge II webbing.
- Tubular edge design with damage-resistant core helps protect the body fibers from cutting, keeping the integrity of the sling intact without compromising its strength.
- Edge Damage Limit (EDL), out-of-service marker aids in sling inspection.
- Soft twill weave body.
- Improved handling characteristics with no coated edge yarns.
- Easy to identify by the blue tubular edges and EDL marker.



Width (in.)	Vertical (lbs.)	Part Number	Sale Price \$								
			3'	4'	6'	8'	10'	12'	14'	16'	20'
1	3,200	EE2801TFX_Length	\$ 9.61	\$ 10.89	\$ 13.47	\$ 16.04	\$ 18.62	\$ 21.19	\$ 23.76	\$ 26.34	\$ 31.48
2	6,400	EE2802TFX_Length	\$ 13.86	\$ 16.19	\$ 20.85	\$ 25.51	\$ 30.17	\$ 34.82	\$ 39.48	\$ 44.13	\$ 53.45
3	8,800	EE2803TFX_Length	\$ 21.67	\$ 25.43	\$ 32.96	\$ 40.49	\$ 48.02	\$ 55.55	\$ 63.08	\$ 70.61	\$ 85.67
4	11,500	EE2804TFX_Length	\$ 29.74	\$ 34.62	\$ 44.39	\$ 54.14	\$ 63.90	\$ 73.66	\$ 83.42	\$ 93.18	\$ 112.70

Please call for sizes not listed.

## TUFLEX® Roundslings

- Double-wall cover for greater sling life.
- Color-coded capacities for quick identification.
- No strength loss from abrasion to cover.
- Chokes tighter and releases easier than other slings.
- Wear points can be shifted to extend sling life.
- Easier to inspect than other slings.



**Special Offer**  
Take another 10% off  
these prices

Color	Vertical (lbs.)	Part Number	Sale Price \$				
			4'	6'	8'	10'	12'
EN30 PURPLE	2,600	EN30X_Length	\$ 10.88	\$ 14.96	\$ 19.05	\$ 23.13	\$ 27.22
EN60 GREEN	5,300	EN60X_Length	\$ 13.20	\$ 18.58	\$ 23.95	\$ 29.33	\$ 34.70
EN90 YELLOW	8,400	EN90X_Length	\$ 17.55	\$ 24.80	\$ 32.05	\$ 39.31	\$ 46.55
EN150 RED	13,200	EN150_Length	\$ 25.95	\$ 36.72	\$ 47.49	\$ 58.25	\$ 69.02

Please call for sizes not listed.

## Permaloc™ Wire Rope Slings

- Reserve strength: Flemish eye splice offers reserve strength should the sleeve become damaged.
- Good abrasion resistance for longer life.
- IWRC resists crushing better than fiber core ropes.
- Tuff-Tag shows the OSHA required capacity information as well as serial-numbered identification for traceability.
- Made in USA from imported rope.
- Good abrasion resistance for longer life.




Please call for sizes not listed.

Rope Dia.	Rated Capacity (tons)			Part Number	Sale Price \$				
	Vertical	Choker	Basket		4'	6'	8'	10'	12'
1/4	.65	.48	1.3	14IEEX_Length	\$ 7.02	\$ 8.07	\$ 9.11	\$ 10.16	\$ 11.21
3/8	1.4	1.1	2.9	38IEEX_Length	\$ 9.61	\$ 11.19	\$ 12.77	\$ 14.35	\$ 15.92
1/2	2.5	1.9	5.1	12IEEX_Length	\$ 13.32	\$ 15.31	\$ 17.30	\$ 19.30	\$ 21.29
3/4	5.6	4.1	11	34IEEX_Length	\$ 28.70	\$ 32.66	\$ 36.62	\$ 40.58	\$ 44.54

## Lever Chain Hoists

- Easy one hand operation and set up.
- Operates in any orientation.
- Non-slip rubber grip lever and 360° rotation require minimal space for operation with 20 to 30% less pull force than other brands.
- Powder-coated and plated finishes resist corrosion.
- Fully enclosed gearing to protect from contamination.
- The automatic Weston style mechanical load brake will react to the inertia of a descending load.
- Drop forged alloy hooks are designed to stretch before chain failure when overloaded and are equipped with cast steel safety latches.
- The top hook mounting articulates to aid in rigging and helps ensure straight line loading between hooks.



MODEL	WLL (lbs.)	LIFT (ft.)	DIMENSIONS (inches)						P (lbs.)	Sale Price \$
			A	B	C	D	E	F		
LCH008	1,650	10	12.6	5.3	5.8	11.4	3.5	0.94	33	\$ 216.13
LCH015	3,300	10	15.0	6.4	6.9	16.5	4.0	1.14	66	\$ 268.39
LCH030	6,600	10	18.9	8.3	7.7	16.5	4.3	1.42	122	\$ 399.08
LCH060	13,200	10	24.4	10.0	7.7	16.5	4.3	1.81	264	\$ 663.47